

Technical Data Sheet

Non-sag PU Construction Sealant

One component PU construction sealant (non-sag)

Data Table:

Note: Values presented hereby are representation of typical properties of the product, actual properties may differ due to the conditions of working zone.

Base	Solvent based
Appearance	Grey paste
Drying time (25 degree Celsius)	Approx 20 minutes
Fully curing time	24 hours
Elongation at break	650%
Viscosity (Cps)	Non-sag
Tensile Strength (kgf/cm ²)	10.5

Please wear protective gloves, masks and eye wear for safety.

Description:

This premium polyurethane sealant is specifically designed for vertical and overhead joint applications in construction. Its advanced formula prevents sagging, ensuring reliable performance even in challenging projects.

Key Features:

- **Non-Sag Formulation:** Specifically designed to stay in place on vertical and overhead surfaces.
- **Excellent Adhesion:** Strongly adheres to concrete, masonry, and other common construction materials.
- **Durable and Flexible:** Maintains integrity and accommodates joint movement over time.
- **Weather Resistant:** Withstands harsh environmental conditions, including UV rays and moisture.

Applications:

- **Vertical Joints:** Ideal for sealing expansion and control joints in walls and facades.
- **Overhead Applications:** Suitable for ceilings and other overhead structures.
- **Masonry Walls:** Perfect for sealing joints in brick and block walls.
- **Airport Runways, Expansion Joints, and Concrete Joints in Marine Port Walkways/driveways.**

Packaging: 300ml cartridge

Shelf Life: 12 months

Storage Conditions:

Store at 25°C in a cool place, away from fire and direct sunlight. Do not store cartridge upside down.